




Derrick 200 DR 5/10 Litronic®













DIN

LIEBHERR

Ausladung und Tragfähigkeit

Radius and capacity / Portée et charge / Sbraccio e portata
Alcances y cargas / Alcance e capacidade de carga / Вылет и грузоподъемность

 ↓ 317,0 m*		mit Stiff-Legs / with 'stiff legs' / avec «stiff-legs» / con Stiff-Legs con stiff-legs / com tirante rígido / с выносными опорами													
m	m/kg	11,0	12,0	13,0	14,0	15,0	16,0	17,0	18,0	19,0	21,0	22,0	23,0	25,0	
25,0	 6,0–25,0 5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	
25,0	 5,8–19,0 10000	10000	10000	10000	10000	10000	10000	10000	10000	10000	8980	8550	8150	24,8 m 7500	
21,0	 5,3–21,0 5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	5000				
21,0	 5,1–20,6 10000	10000	10000	10000	10000	10000	10000	10000	10000	10000	20,6 m 10000				




 ↓ 317,0 m*		ohne Stiff-Legs / without 'stiff legs' / sans «stiff-legs» / senza Stiff-Legs sin stiff-legs / sem tirante rígido / без выносных опор													
m	m/kg	11,0	12,0	13,0	14,0	15,0	16,0	17,0	18,0	19,0	21,0	22,0	23,0	25,0	
25,0	 6,0–20,0 5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	4700	4480	4250	3800	
25,0	 5,8–10,9 10000	9890	8830	7960	7220	6600	6060	5590	5180	4810	4190	3920		24,8 m 3300	
21,0	 5,3–21,0 5000	5000	5000	5000	5000	5000	5000	5000	5000	5000	5000				
21,0	 5,1–11,1 10000	10000	9050	8190	7450	6820	6280	5810	5390	5020	20,6 m 4500				




Zug-/Druckkräfte an den Verankerungspunkten auf Anfrage. / Tension/compression forces at anchoring points on request. / Forces de traction/compression aux points d'ancrage sur demande. / Sforzi di trazione e pressione sui punti di ancoraggio, su richiesta. / Fuerzas de tracción y compresión sobre los puntos de anclaje, consulta previa. / Forças de tração e compressão nos pontos de ancoragem, mediante consulta. / Усилия растяжения/сжатия в точках крепления - по запросу.


***Tragfähigkeit für höhere Hubhöhen auf Anfrage.** / Lifting capacity for higher hoisting heights on request. / Capacité de levage pour des hauteurs de levage plus hautes sur demande. / Portata per elevate altezze gancio su richiesta. / Consultar cargas máximas para alturas bajo gancho superiores. / Capacidade de carga para maiores alturas sob consulta. / Грузоподъемность для большой высоты подъема по запросу.

Antriebe

Driving units / Mécanismes d'entraînement / Meccanismi / Mecanismos / Mecanismos / Приводы

 180°	U/min 0 ↔ 0,8 sl./min tr./min	1 x 5,0 kW FU	 45 kW FU
 1,3 min.		37 kW FU	
			kVA 72,0

	 max. 633 m	↔ stufenlos / stepless / régl. continu / regl. progressiva / sin escalones sem degraus / Бесступенчатый	kg	m/min	kg	m/min
45 kW FU WIW 260 MZ 407 	10 Lagen Layers / Couches Strati / Camadas Capas / Слоев		1 4900 200	0 ↔ 44 0 ↔ 172	1 10000 1000	0 ↔ 22 0 ↔ 100



Konstruktionsänderungen vorbehalten! / Subject to alterations!
Sous réserves de modifications! / Si fa riserva di modifiche!
¡Sujeto a modificaciones! / Salvo modificação da construo!
Права на внесение конструкторских изменений сохраняются!

Sämtliche Angaben erfolgen ohne Gewähr. / This information is supplied without liability. / Ces renseignements sont sans garantie. / Le indicazioni contenute si intendono salvo errori ed omissioni. Declinamos toda responsabilidad derivada de la información proporcionada. / Declinamos qualquer responsabilidade quanto à informação fornecida. / Все данные указаны без обязательств.

110 P – 4856 H1 B3 DIN 15018 • BGL C.1.31.1020 • 01.09/7

Printed in Germany.